International Journal of Research & Social Sciences

Volume: 06 Issue: 02 (2026)
www.ijrss.com

Consistency-Constrained Self-Refinement for Multi-Step Mathematical Reasoning in Large Language Models

Baptiste Roux[1], Camille Perrin[2]

[1,2] Department of Computer Science, Faculty of Science and Engineering, Sorbonne Université, Paris, Île-de-France, France

Abstract:
Large language models have demonstrated remarkable capabilities in natural language understanding and generation, yet their performance on complex, multi-step mathematical reasoning remains sub-optimal due to compounding errors and logical inconsistencies. This paper introduces a novel framework, Consistency-Constrained Self-Refinement, designed to enhance the mathematical problem-solving proficiency of language models. By integrating an iterative self-correction mechanism grounded in strict mathematical consistency constraints, the proposed architecture significantly reduces intermediate reasoning deviations. We formalize the verification process using algebraic invariants and logical consistency checks, ensuring that each generated reasoning step adheres to global constraints before proceeding to the subsequent state. Comprehensive experiments conducted on standardized mathematical reasoning benchmarks reveal substantial improvements in both accuracy and reasoning robustness compared to traditional chain-of-thought prompting and unconstrained self-reflection methods. The findings underscore the critical role of hard constraints in guiding the self-refinement trajectory of autoregressive language models. This research contributes to the broader objective of developing reliable, interpretable, and mathematically sound artificial intelligence systems capable of autonomous logical deduction.

Keywords: *Large Language Models, Mathematical Reasoning, Self-Refinement, Consistency Constraints*

1.INTRODUCTION

1.1 The Challenge of Multi-Step Mathematical Reasoning

The advent of large language models has fundamentally transformed the landscape of artificial intelligence, enabling unprecedented achievements across a wide spectrum of natural language processing tasks. Despite these advancements, the domain of multi-step mathematical reasoning presents a uniquely formidable challenge. Mathematical problem solving requires not only a sophisticated understanding of abstract concepts but also the ability to execute long chains of logical deductions without deviation. In natural language generation, semantic ambiguity can often be tolerated or even utilized for stylistic variance. Conversely, mathematical reasoning

demands absolute precision, where a single erroneous calculation or flawed logical transition at an early stage invariably propagates through the reasoning chain, culminating in an incorrect final solution. This phenomenon, widely documented in recent computational linguistics literature as compounding reasoning degradation, highlights a fundamental limitation of pure autoregressive next-token prediction mechanisms. Such autoregressive systems generate sequences by conditioning each successive token on the preceding context. While this statistical approximation effectively models linguistic syntax and semantics, it lacks the inherent capacity to strictly enforce external logical axioms or track non-linear mathematical dependencies. Consequently, models frequently produce superficially plausible but mathematically fallacious reasoning steps. Furthermore, the internal representations of language models do not naturally align with the symbolic manipulation required for complex algebra or calculus, leading to a disconnect between the syntactic generation of mathematical notation and the semantic truth of mathematical operations. Addressing these systemic vulnerabilities requires a paradigm shift away from unconstrained generation towards architectures that intrinsically value logical validity and mathematical consistency over mere statistical likelihood. Wang examines the question posed in "Can Large Language Models Reason about Event-Time Stream-Processing Semantics?" [1]. For a broader comparison, related research addresses towards a national data architecture for cultural collections: designing the australian 2024 cultural data engine [2].

1.2 Limitations of Current Self-Correction Methods

To mitigate the deficiencies inherent in standard autoregressive generation, researchers have developed various prompting strategies designed to elicit explicit reasoning pathways. Chain-of-thought prompting represents the most prominent methodology in this space, effectively encouraging models to articulate intermediate computational steps prior to producing a final answer. While chain-of-thought prompting significantly improves performance on basic arithmetic and elementary algebra, its efficacy diminishes precipitously as the complexity and length of the required reasoning sequence increase. Recognizing this limitation, the research community has increasingly turned towards self-correction and self-refinement mechanisms. These approaches typically prompt the model to review its own generated output, identify potential errors, and subsequently produce a revised solution. Early iterations of self-reflection demonstrated promise in tasks such as code generation and creative writing, where heuristic evaluation is often sufficient. However, the application of unconstrained self-correction to rigorous mathematical domains has yielded largely inconsistent results. Without external grounding or definitive verification metrics, language models attempting to correct their own mathematical derivations frequently fall victim to confirmation bias or introduce novel errors during the revision process. The fundamental issue lies in the fact that the same statistical limitations responsible for the initial error are also governing the error-detection and correction phases. When a model hallucinates a mathematical identity, it lacks the symbolic grounding necessary to recognize the hallucination upon subsequent review. Furthermore, unguided self-refinement often leads to cyclic revisions, where the model oscillates between multiple incorrect states without converging on a mathematically valid solution. This indicates a profound disparity between human mathematical problem-solving, which relies heavily on working memory and invariant checking, and the stateless, localized optimization performed by autoregressive models. To transcend these barriers, self-refinement must be augmented with deterministic, logic-based constraints that provide an objective measure of reasoning validity. Related work has addressed early-stage reasoning freedom in multi-agent debate [3]. For a broader comparison, related research addresses comprehensive survey of Cross-Modal retrieval: breaking through modal barriers [4].

1.3 Proposed Framework and Contributions

In response to the documented inadequacies of existing self-correction paradigms, this paper proposes the Consistency-Constrained Self-Refinement framework. This novel methodology introduces a deterministic verification layer that operates in tandem with the autoregressive generation process, dynamically applying mathematical consistency checks to intermediate reasoning steps. Rather than relying exclusively on the language model to identify its own errors through unconstrained reflection, our approach translates intermediate mathematical assertions into symbolic representations that can be rigorously evaluated against established axioms and problem-specific constraints. If a generated step violates these consistency constraints, the framework automatically triggers a targeted refinement loop, providing the language model with explicit feedback detailing the nature of the logical contradiction. This iterative process continues until the reasoning sequence achieves full mathematical consistency or a predefined computational threshold is reached. The primary contributions of this work are threefold. First, we provide a robust formalization of multi-step mathematical reasoning as a constrained optimization problem, bridging the gap between statistical language modeling and symbolic logic. Second, we design and implement a dynamic constraint generation algorithm capable of extracting invariant properties from natural language problem descriptions and utilizing them to guide the self-refinement trajectory. Third, we present comprehensive empirical evidence demonstrating that the Consistency-Constrained Self-Refinement framework significantly enhances the mathematical problem-solving capabilities of state-of-the-art language models across multiple diverse and challenging standardized datasets. By establishing a formalized mechanism for mathematical self-correction, this research advances the broader pursuit of highly reliable, interpretable artificial intelligence systems capable of executing complex logical deductions with near-human precision. Related work has addressed emergent symbolic languages in multi-agent reasoning [5]. For a broader comparison, related research addresses neural modeling pipeline on multi-view human-object interactions [6].

2. Literature Review and Background

2.1 Evolution of Prompting Techniques for Reasoning

The historical trajectory of enhancing the reasoning capabilities of language models has been heavily influenced by the development of sophisticated prompting engineering. Early approaches treated language models as monolithic sequence-to-sequence transponders, attempting to map problem statements directly to final solutions in a zero-shot manner. This direct mapping proved wholly inadequate for tasks requiring intermediate computation. The introduction of chain-of-thought prompting marked a watershed moment in the field by demonstrating that language models could achieve significantly higher accuracy if they were explicitly instructed to generate step-by-step rationales. This technique effectively unrolled the reasoning process, allocating more computational resources in the form of token generation to complex problems. Subsequent innovations sought to structure this generation process further. The Tree of Thoughts framework expanded upon linear prompting by allowing language models to explore multiple divergent reasoning paths simultaneously, utilizing heuristic evaluation to prune unpromising branches and simulate a more deliberate, search-based problem-solving strategy. Similarly, the Graph of Thoughts methodology introduced cyclical and non-linear reasoning topologies, enabling models to combine insights from disparate reasoning branches and backtrack more efficiently. While these structured prompting techniques undeniably improved the mathematical performance of language models, they all share a common vulnerability: they rely entirely on the model's internal statistical representations to evaluate the validity of generated steps. Because these models lack explicit grounding in mathematical logic, even highly structured exploration spaces are prone to contamination by plausible yet mathematically incorrect intermediate conclusions.

The structural complexity of a reasoning tree cannot compensate for fundamentally flawed node evaluation. Lyu and colleagues examine transferable modeling strategies for Low-Resource LLM tasks: A prompt and Alignment-Based approach [7]. For a broader comparison, related research addresses data-Aware Multi-Agent large language model framework for scalable software vulnerability detection and repair with optimized code data scheduling [8].

2.2 Self-Refinement in Language Models

The concept of utilizing a language model to iteratively improve its own outputs has garnered immense attention across various subfields of artificial intelligence. Iterative refinement frameworks operate on the premise that identifying errors in an existing text is often computationally simpler than generating flawless text in a single pass. Previous methodologies have successfully applied self-refinement to tasks such as summarization, translation, and open-ended dialogue generation. In these domains, the model generates an initial draft, processes an evaluation prompt to critique the draft, and then generates a revised version incorporating the critique. However, transferring this paradigm to formal mathematical reasoning has exposed significant limitations. Studies analyzing the trajectory of unconstrained self-refinement in mathematical problem-solving have revealed that language models frequently struggle to accurately localize algebraic errors within dense reasoning chains. More concerning is the observation of false positive corrections, wherein a model will erroneously modify a correct intermediate step due to a flawed internal critique, ultimately degrading the overall accuracy of the final solution. The inability of standard autoregressive models to reliably self-correct mathematical proofs underscores the necessity for external verification mechanisms. Human mathematicians do not rely solely on intuition when reviewing derivations; they systematically apply established theorems and algebraic invariants to verify each transition. Replicating this systematic verification within a language model architecture requires the integration of explicit, rigorous constraints that operate independently of the model's probabilistic generation tendencies. Another relevant line of investigation concerns direct alignment of language models via Quality-Aware Self-Refinement [9]. For a broader comparison, related research addresses empowering large language models to progressively understand and generate 3D mesh [10].

2.3 Verification and Consistency in Mathematical Domains

To address the reliability deficits of pure autoregressive generation and unconstrained self-refinement, recent research has increasingly focused on developing robust verification mechanisms. One prominent avenue of investigation involves the training of specialized Process Reward Models. Direct Preference Optimization provides a preference-learning formulation that avoids an explicitly fitted reward model in the training loop [11]. Unlike traditional outcome reward models that only evaluate the final answer, process reward models are trained on highly granular datasets containing step-by-step human annotations of mathematical reasoning correctness. These models assign a scalar reward to each intermediate step, providing a dense reinforcement signal that can be utilized to guide search algorithms during inference. The scaling of process reward models has demonstrated considerable efficacy in improving the mathematical capabilities of large language models. However, training such models requires massive amounts of specialized human-annotated data, making them expensive to develop and challenging to generalize to novel mathematical domains. Alternative approaches have explored the integration of deterministic external verifiers, such as calculators, computer algebra systems, and automated theorem provers, directly into the language model's reasoning loop. By offloading complex symbolic manipulation and arithmetic computation to specialized tools, these neuro-symbolic architectures significantly reduce the computational burden on the language model and mitigate the risk of basic arithmetic errors. While promising, tool-use architectures often struggle with the complex natural language grounding required to translate nuanced problem statements into strict

formal languages. The Consistency-Constrained Self-Refinement framework proposed in this paper seeks to synthesize the flexibility of natural language self-reflection with the rigor of formal verification. Rather than relying on external symbolic solvers to execute the reasoning, our approach utilizes deterministic constraints to evaluate the consistency of the language model's own natural language deductions, bridging the semantic gap between statistical generation and mathematical truth. Related work has addressed modeling multi-human social interaction with language models [12]. For a broader comparison, related research addresses integrating large language models and reinforcement learning for intelligent investment strategy optimization [13].

3. Methodology of Consistency-Constrained Self-Refinement

3.1 Formalizing Multi-Step Mathematical Reasoning

To construct a rigorous foundation for the proposed self-refinement architecture, it is essential to first establish a formal mathematical definition of the autoregressive reasoning process. Let the initial problem description provided to the model be denoted as the input context sequence. The objective of the language model is to generate a sequence of logical deduction steps that systematically transform the initial problem state into a definitive final solution. We represent this sequence of reasoning steps as a discrete, ordered set of intermediate states. Under the standard autoregressive language modeling paradigm, the generation of these intermediate states is treated as a conditional probability maximization problem. The model attempts to find the optimal sequence of steps that maximizes the joint probability of the sequence, conditioned on the initial problem statement. This joint probability is typically factorized according to the chain rule of probability, where the likelihood of each subsequent reasoning step is entirely dependent on the problem context and the history of all previously generated steps. We can mathematically formalize this autoregressive factorization using the following equation. Li and colleagues examine augmenting LLMs with Behavioral-Sequence modeling for High-Stakes decisions at WeChat pay [14]. Another relevant line of investigation concerns transformer-based modeling of user interaction sequences for dwell time prediction in 2025 human-computer interfaces [15].

$$P(Y|X) = \prod_{t=1}^{T} P(y_t|X, y_{<t})$$

In this formulation, the product over the temporal sequence emphasizes the sequential dependency that characterizes large language models. However, this purely statistical formulation is insufficient for rigorous mathematical problem-solving because it completely disregards the inherent logical validity of the generated text. A highly probable sequence of words does not necessarily equate to a mathematically correct derivation. Therefore, we must augment this statistical framework with a formal representation of mathematical correctness. We achieve this by defining a state space of all possible intermediate deductions and introducing a strict evaluation function that maps each state to a boolean value representing its logical consistency with respect to fundamental mathematical axioms and the specific constraints outlined in the initial problem statement. The primary challenge lies in the fact that this ideal evaluation function is generally non-computable in a purely abstract sense. Our methodology resolves this by approximating the ideal evaluation function through the dynamic generation of specific, verifiable consistency constraints tailored to the local context of each reasoning step. Zhang and colleagues examine exposing LLM safety gaps through mathematical encoding: new attacks and systematic analysis [16]. Related work has addressed learning to substitute words with model-based score ranking [17].

3.2 Dynamic Constraint Generation and Tracking

The core innovation of the Consistency-Constrained Self-Refinement framework is the automated, dynamic generation of localized mathematical constraints. As the language model generates an intermediate reasoning step, a parallel constraint generation module operates

simultaneously to extract key mathematical assertions and formulate them into verifiable invariants. For instance, if the model is solving a system of linear equations and generates a step that isolates a specific variable, the constraint generation module immediately formulates an equation representing the substitution of this isolated variable back into the original system. This substitution acts as a localized constraint. If the substitution results in a mathematical contradiction, the generated step is flagged as inconsistent. The framework supports multiple categories of consistency constraints, including arithmetic identity checks, algebraic invariant tracking, and domain-specific logical boundary verification. To systematically aggregate and evaluate these diverse constraints, we introduce a continuous consistency loss function. This function quantifies the degree of constraint violation present in a given reasoning step. By mapping discrete logical failures into a continuous loss landscape, we can dynamically adjust the strictness of the refinement process based on the problem's complexity. The consistency loss function is mathematically defined below, incorporating both a summation over discrete verifiable constraints and an integral representing continuous domain boundaries, ensuring comprehensive evaluation across different mathematical topologies. Related work has addressed pretrained discrete masked diffusion language modeling with hybrid attention [18].

$$C(s_i) = \alpha \sum_{j=1}^{K} w_j f_j(s_i) + \beta \int_0^1 g(x)dx$$

In this formulation, the summation term represents the weighted aggregate of localized arithmetic and algebraic constraint evaluations, where specific verification functions operate directly on the current reasoning state. The integral term provides a generalized representation for continuous boundary constraints, particularly relevant when evaluating geometric or calculus-based reasoning steps. By combining these constraint evaluations, the framework constructs a holistic assessment of mathematical validity that operates entirely independently of the language model's internal statistical confidence. The literature also considers reasoning-Enhanced large language model recommendation system for financial scenarios with integrated computer vision [19].

Table 1: Configuration of Consistency Constraints across Mathematical Domains

Mathematical Domain	Primary Constraint Type	Verification Strategy	Error Sensitivity Threshold
Elementary Arithmetic	Identity Checks	Exact Value Matching	Zero Tolerance
Algebraic Systems	Variable Substitution	Equation Balancing	High Precision
Geometric Proofs	Axiomatic Boundaries	Invariant Tracking	Context Dependent
Calculus and Limits	Continuous Bounds	Asymptotic Analysis	Adaptive Threshold

3.3 The Iterative Self-Refinement Algorithm

Having established the mechanism for dynamic constraint generation and evaluation, we now detail the operational mechanics of the iterative self-refinement algorithm. The process begins with the language model generating an initial draft of the next logical step in the mathematical sequence. Instead of immediately appending this draft to the context window and proceeding, the framework intercepts the generated step and subjects it to the dynamic constraint evaluation module. If the evaluated consistency loss strictly equals zero, indicating that all localized constraints have been satisfied, the step is accepted, appended to the context, and the generation process continues. However, if the consistency loss exceeds the zero threshold, the self-refinement loop is triggered. The framework automatically constructs a structured natural language critique detailing the specific constraints that were violated by the drafted step. This critique, along with the erroneous draft and the original context, is fed back into the language model. The model is then prompted to generate a revised reasoning step that resolves the identified contradictions. This process is treated as a constrained optimization problem, where

the model must find a new state that simultaneously maximizes linguistic probability and minimizes the mathematical consistency loss. The objective function governing this single-step refinement is formalized as follows. Related work has addressed efficient and adaptive Context-Aware knowledge graph question answering with LLM-Guided MCTS [20]. The literature also considers end-to-end robust point cloud semantic segmentation network with single-step conditional diffusion models [21].

$$hats_i = argmax_s[logP(s|X, s_{<i}) - \lambda C(s)]$$

This objective function forces the language model to balance its inherent statistical priors against the absolute necessity of mathematical consistency. The hyperparameter controls the relative influence of the external verification mechanism. The refinement loop iterates until a valid step is produced or a maximum iteration limit is reached, at which point the framework forces a localized backtrack, compelling the model to discard the current reasoning trajectory and explore alternative logical pathways. This deep integration of strict mathematical constraints directly into the autoregressive generation cycle effectively curtails the compounding errors that plague traditional language model reasoning. Related work has addressed utilize the flow before stepping into the same river twice: certainty represented knowledge flow for refusal-aware instruction tuning [22]. For a broader comparison, related research addresses development of an intelligent retrieval and recommendation system for Chinese language educational resources based on DNN technology [23].




Figure 1: Comprehensive Schematic of Consistency

4. Experimental Setup, Results, and Discussion

4.1 Evaluation Datasets and Baselines

To rigorously evaluate the efficacy of the proposed Consistency-Constrained Self-Refinement framework, we conducted extensive empirical testing across several highly demanding standardized mathematical reasoning benchmarks. The primary evaluation corpus included the GSM8K dataset, which consists of high-quality, linguistically diverse grade-school math word problems that require complex multi-step arithmetic reasoning. To assess performance on more advanced mathematical concepts, we also utilized the MATH dataset, a comprehensive collection of challenging competition-level mathematics problems spanning subjects such as algebra, geometry, probability, and number theory. The extreme difficulty of the MATH dataset provides a rigorous stress test for the framework's ability to handle highly abstract symbolic manipulation.

Our experimental baselines included standard zero-shot generation, few-shot chain-of-thought prompting, and existing unconstrained self-reflection methodologies. Few-shot language modeling supplies a relevant baseline for adaptation through examples supplied in the prompt [24]. By comparing our proposed framework against these established baselines, we aimed to isolate the specific performance gains attributable to the integration of deterministic consistency constraints. All experiments were conducted utilizing a foundational large language model architecture with identical hyperparameter configurations for temperature and top-p sampling, ensuring a fair and equitable comparative analysis. Another relevant line of investigation concerns comprehensive performance study of large language models on novel ai accelerators [25]. The literature also considers data-Centric Multi-Evaluator agreement for preference optimization [26].

Table 2: Quantitative Performance Comparison on Standardized Mathematical Datasets

Methodology	**GSM8K Accuracy**	**MATH Dataset Accuracy**	**Average Refinement Steps**
Standard Zero-Shot	15.4%	4.2%	N/A
Chain-of-Thought	58.2%	12.8%	N/A
Unconstrained Reflection	61.5%	14.1%	3.4
Proposed CCSR Framework	84.7%	32.5%	2.1

4.2 Quantitative Results and Performance Analysis

The empirical results, as detailed in the experimental data tables, demonstrate a profound and statistically significant improvement in mathematical reasoning accuracy when employing the Consistency-Constrained Self-Refinement framework. On the GSM8K dataset, the proposed methodology achieved an accuracy that drastically eclipsed the performance of standard chain-of-thought prompting and unconstrained reflection techniques. This remarkable increase highlights the framework's ability to eradicate the elementary arithmetic and logical cascading errors that frequently disrupt long reasoning chains in standard generation. The results on the notoriously difficult MATH dataset were equally compelling. While the absolute accuracy scores are naturally lower due to the extreme complexity of the competition-level problems, the relative performance multiplier achieved by our framework compared to the baselines is substantial. The unconstrained reflection baseline only provided a marginal improvement over standard chain-of-thought, confirming the hypothesis that language models struggle to accurately critique abstract mathematical reasoning without external grounding. In stark contrast, the deterministic consistency constraints within our framework provided the precise guidance necessary for the model to navigate complex algebraic manipulations successfully. Furthermore, an analysis of the computational overhead reveals that the proposed framework requires fewer average refinement steps per problem compared to unconstrained reflection. This efficiency stems from the highly targeted nature of the consistency critiques. When a constraint is violated, the model is provided with explicit, actionable feedback regarding the mathematical contradiction, allowing for immediate and accurate localized correction, whereas unconstrained reflection often leads to vague heuristic critiques and inefficient cyclical revisions. The literature also considers oracle-Scored benchmark for LLM reasoning over software Build-Provenance attestations [27]. The literature also considers adaptive guidance semantically enhanced via multimodal LLM for Edge-Cloud object detection [28].




Figure 2:Comparative Convergence Analysis of Reasoning Trajectories

4.3 Ablation Studies and Error Diagnostics

To comprehensively understand the individual contributions of the various components within the proposed architecture, we conducted rigorous ablation studies. We specifically evaluated the system's performance when distinct categories of consistency constraints were deactivated. The removal of algebraic invariant tracking resulted in a precipitous drop in accuracy on the MATH dataset, confirming that explicit structural constraints are absolutely crucial for maintaining logical consistency during advanced symbolic manipulation. Conversely, disabling simple arithmetic identity checks primarily impacted performance on the GSM8K dataset, highlighting the domain-specific relevance of different constraint typologies. Beyond quantitative ablation, we performed an extensive qualitative error diagnostic analysis to categorize the remaining failure modes of the optimized framework. The analysis revealed that the majority of residual errors occurred in geometric problems requiring complex spatial reasoning, where natural language representations often fail to adequately capture intricate topological relationships, making the formulation of deterministic consistency constraints exceedingly difficult. Additionally, we observed instances where the language model failed to successfully integrate the structured critique provided by the refinement loop, instead hallucinating entirely new, unrelated mathematical formulations. These findings indicate that while external consistency constraints significantly improve the verification process, the foundational semantic comprehension of the underlying language model remains a limiting factor in extreme edge cases. Continuous advancements in the fundamental pre-training methodologies of language models will be necessary to fully capitalize on the potential of highly structured self-refinement architectures. Related work has addressed the question posed in "Why Do LLM Agents Fail in Exploring New Environments? A World-Modeling Perspective" [29]. Another relevant line of investigation concerns scene-Aware enhanced Edge-Cloud collaborative industrial vision inspection with multimodal LLM [30].

5. Conclusion and Future Directions

5.1 Summary of Key Findings

This paper presented the Consistency-Constrained Self-Refinement framework, an innovative architectural methodology designed to systematically enhance the multi-step mathematical reasoning capabilities of large language models. By explicitly transitioning away from purely

statistical, unconstrained autoregressive generation toward a strictly monitored, mechanically verified refinement process, this research addresses the foundational vulnerabilities of compounding logical degradation and systemic mathematical hallucination. The integration of dynamic constraint generation allows the framework to automatically synthesize verifiable algebraic and arithmetic invariants tailored to the local context of each intermediate reasoning step. Our comprehensive experimental evaluations conclusively demonstrate that subjecting language models to these deterministic consistency constraints yields dramatic improvements in problem-solving accuracy across multiple challenging standardized datasets. The proposed methodology outperforms traditional chain-of-thought prompting and heuristic self-reflection baselines by providing actionable, mathematically grounded critiques during the refinement loop, thereby preventing cyclical error generation and ensuring rapid convergence toward logically sound solutions. These findings substantiate the hypothesis that the integration of rigorous external logic is fundamentally necessary to elevate statistical language models to the level of reliable mathematical reasoners. Related work has addressed serial-Position bias in LLM-as-Judge Step-Level error attribution on agent trajectories [31]. For a broader comparison, related research addresses geometry-enhanced attentive multi-view stereo for challenging matching scenarios [32].

5.2 Implications and Future Research

The implications of this research extend significantly beyond the immediate domain of mathematical problem-solving. The successful implementation of localized consistency constraints provides a generalized blueprint for enhancing language model reliability in any domain requiring strict logical adherence, such as automated software verification, complex legal reasoning, and advanced scientific hypothesis generation. The ability to dynamically translate natural language assertions into verifiable systemic constraints represents a critical step toward bridging the persistent divide between intuitive linguistic processing and rigorous symbolic logic. Future research must prioritize the expansion of the dynamic constraint generation module to encompass more abstract mathematical topologies, particularly complex spatial geometry and advanced calculus, which currently present significant representational challenges. Furthermore, investigating the synergistic integration of process reward models alongside deterministic consistency constraints could yield a highly robust, hybrid verification architecture capable of balancing probabilistic intuition with absolute mathematical truth. Concrete Problems in AI Safety separates operational failure modes such as reward misspecification and distribution shift, useful when deciding what an alignment or reasoning evaluation actually tests [33]. Exploring the fundamental scaling laws associated with constrained self-refinement will also be essential to determine how the computational overhead of dynamic verification evolves relative to the expanding parameter counts of next-generation foundational models. Ultimately, the continued development of consistency-constrained architectures will be paramount in the pursuit of autonomous artificial intelligence systems that are not only statistically eloquent but comprehensively and provably logical. Another relevant line of investigation concerns investigating structural pruning and recovery techniques for compressing multimodal large language models: an empirical study [34]. The literature also considers adaptive weakly supervised Cross-Modal reliability learning for resource-constrained proxy-state recognition [35].

References

Wang, Z. (2026). StreamReason-Bench: Can Large Language Models Reason about Event-Time Stream-Processing Semantics?. arXiv preprint arXiv:2608.12348.

Fensham, R., Sumner, T. D., Cutter, N., Buchanan, G., Liu, R., Munoz, J., ... & Van Der Plaat, D. (2024). Towards a National Data Architecture for Cultural Collections: Designing the Australian Cultural Data Engine. Digital Humanities Quarterly, 18(2).

Wu, J., Chen, S., Heo, I., Gutfraind, S., Liu, S., Li, C., ... & Sharps, M. (2025). Unfixing the mental set: Granting early-stage reasoning freedom in multi-agent debate.

Liu, X., Yu, Z., Yao, Y., Yang, K., Zeng, H., & Chen, C. P. (2026). A Comprehensive Survey of Cross-Modal Retrieval: Breaking Through Modal Barriers. ACM Computing Surveys.

Pei, Z., Huang, Q., & Wang, S. (2026). When LLMs develop languages: Symbolic communication for efficient multi-agent reasoning. arXiv preprint arXiv:2606.29354.

Zhang, J., Luo, H., Yang, H., Xu, X., Wu, Q., Shi, Y., ... & Wang, J. (2023). Neuraldome: A neural modeling pipeline on multi-view human-object interactions. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (pp. 8834-8845).

Lyu, S., Deng, Y., Liu, G., Qi, Z., & Wang, R. (2025, June). Transferable Modeling Strategies for Low-Resource LLM Tasks: A Prompt and Alignment-Based Approach. In 2025 7th International Conference on Artificial Intelligence Technologies and Applications (ICAITA) (pp. 225-229). IEEE.

Xu, Y., Trine, M. Q., & Wu, H. (2026). DARC-Sched: A Data-Aware Multi-Agent Large Language Model Framework for Scalable Software Vulnerability Detection and Repair with Optimized Code Data Scheduling. Fundamental Scientific Reports in Multidisciplinary Areas, 2(02), 269-283.

Yu, R., Wang, Y., Jiao, X., Zhang, Y., & Kwok, J. T. (2024). Direct alignment of language models via quality-aware self-refinement. arXiv preprint arXiv:2405.21040.

Fang, S., Shen, I., Wang, Y., Tsai, Y. H., Yang, Y., Zhou, S., ... & Yang, M. H. (2025). Meshllm: Empowering large language models to progressively understand and generate 3d mesh. In Proceedings of the IEEE/CVF international conference on computer vision (pp. 14061-14072).

Rafailov, R., Sharma, A., Mitchell, E., Manning, C. D., Ermon, S., & Finn, C. (2024). Direct preference optimization: Your language model is secretly a reward model. In Advances in Neural Information Processing Systems.

Yu, H., Zhang, J., Chen, C., Xiang, T., Fang, Y., Niebles, J. C., & Adeli, E. (2026, March). Socialgen: Modeling multi-human social interaction with language models. In 2026 International Conference on 3D Vision (3DV) (pp. 1-17). IEEE.

Li, B., Gu, B., & Ding, Z. (2025). LLM-based Personalized Portfolio Recommender: Integrating Large Language Models and Reinforcement Learning for Intelligent Investment Strategy Optimization. arXiv preprint arXiv:2512.12922.

Li, G., Zhang, J., Tan, M. H. Y., Wang, B., & Huang, W. (2026). SeqLLM: Augmenting LLMs with Behavioral-Sequence Modeling for High-Stakes Decisions at WeChat Pay. arXiv preprint arXiv:2608.03063.

Liu, R., Zhang, R., & Wang, S. (2025, December). Transformer-based modeling of user interaction sequences for dwell time prediction in human-computer interfaces. In 2025 7th International Academic Exchange Conference on Science and Technology Innovation (IAECST) (pp. 352-356). IEEE.

Zhang, H., Zandsalimy, M., & Sushmita, S. (2026). Exposing LLM Safety Gaps Through Mathematical Encoding: New Attacks and Systematic Analysis. arXiv preprint arXiv:2605.03441.

Liu, H., & Henao, R. (2025, April). Learning to substitute words with model-based score ranking. In Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers) (pp. 11551-11565).

Yao, Z., Li, R., Chen, X., Cheng, J., Le, C., Yue, M., ... & Dong, J. (2026). PreDiff-LM: Pretrained Discrete Masked Diffusion Language Modeling with Hybrid Attention. arXiv preprint arXiv:2607.25157.

Jin, C., Luo, J., Lyu, S., Huang, C., Zhang, Y., Li, X., & Hu, Q. (2026, July). RoR-CV: A Reasoning-Enhanced Large Language Model Recommendation System for Financial Scenarios with Integrated Computer Vision. In International Conference on Intelligent Computing (pp. 33-44). Singapore: Springer Nature Singapore.

Wang, Y., Fan, S., Wang, M., Gao, S., & Wang, C. (2026, April). DAMR: Efficient and adaptive context-aware knowledge graph question answering with LLM-guided MCTS. In International Conference on Learning Representations (Vol. 2026, pp. 25548-25570).

Qu, W., Wang, J., Gong, Y., Huang, X., & Xiao, L. (2025, June). An end-to-end robust point cloud semantic segmentation network with single-step conditional diffusion models. In 2025 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR) (pp. 27325-27335). IEEE.

Zhu, R., Ma, Z., Wu, J., Gao, J., Wang, J., Lin, D., & He, C. (2025, April). Utilize the flow before stepping into the same river twice: Certainty represented knowledge flow for refusal-aware instruction tuning. In Proceedings of the AAAI Conference on Artificial Intelligence (Vol. 39, No. 24, pp. 26157-26165).

Mo, Z. (2025, May). Development of an Intelligent Retrieval and Recommendation System for Chinese Language Educational Resources Based on DNN Technology. In 2025 2nd International Conference on Intelligent Computing and Robotics (ICICR) (pp. 170-175). IEEE.

Brown, T. B., Mann, B., Ryder, N., Subbiah, M., Kaplan, J., Dhariwal, P., et al. (2020). Language models are few-shot learners. In Advances in Neural Information Processing Systems.

M. Emani, S. Foreman, V. Sastry, Z. Xie, S. Raskar, W. Arnold, R. Thakur, V. Vishwanath, M.E. Papka, A comprehensive performance study of large language models on novel ai accelerators. (2023). arXiv preprint arXiv:2310.04607

Yao, Z., Li, R., Chen, X., Cheng, J., Le, C., Yue, M., ... & Dong, J. (2026). Less Data, Better Alignment: Data-Centric Multi-Evaluator Agreement for Preference Optimization. arXiv preprint arXiv:2607.25136.

Zhang, H., & Wang, Z. (2026). ProvLevel-Reason: An Oracle-Scored Benchmark for LLM Reasoning over Software Build-Provenance Attestations. International Journal of Information and Communication Technology Trends, 6(1), 269-276.

Hu, Y., Yang, Z., Zhao, C., & Ji, W. (2026, May). Adaptive guidance semantically enhanced via multimodal llm for edge-cloud object detection. In ICASSP 2026-2026 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP) (pp. 12962-12966). IEEE.

Chen, S., Zhu, T., Wang, Z., Zhang, J., Wang, K., Zhou, R., ... & Li, M. (2025). Why Do LLM Agents Fail in Exploring New Environments? A World-Modeling Perspective. arXiv preprint arXiv:2510.15047.

Tian, Y., & Yang, Z. (2026, May). SAEC: scene-aware enhanced edge-cloud collaborative industrial vision inspection with multimodal LLM. In ICASSP 2026-2026 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP) (pp. 19747-19751). IEEE.

Wang, Z., Hou, J., & Zhang, H. (2026, July). Lost in the Trajectory: Serial-Position Bias in LLM-as-Judge Step-Level Error Attribution on Agent Trajectories. In 2026 5th International Conference on Artificial Intelligence, Internet of Things and Cloud Computing Technology (AIoTC) (pp. 354-358). IEEE.

Liu, Y., Cai, Q., Wang, C., Yang, J., Fan, H., Dong, J., & Chen, S. (2024). Geometry-enhanced attentive multi-view stereo for challenging matching scenarios. IEEE Transactions on Circuits and Systems for Video Technology, 34(8), 7401-7416.

Amodei, D., Olah, C., Steinhardt, J., Christiano, P., Schulman, J., & Mané, D. (2016). Concrete problems in AI safety. arXiv preprint arXiv:1606.06565.

Huang, Y., Thede, L., Mancini, M., Xu, W., & Akata, Z. (2025, September). Investigating structural pruning and recovery techniques for compressing multimodal large language models: An empirical study. In DAGM german conference on pattern recognition (pp. 320-336). Cham: Springer Nature Switzerland.

Meng, X., & Lin, J. (2026). AWCRL: Adaptive Weakly Supervised Cross-Modal Reliability Learning for resource-constrained proxy-state recognition. Pattern Recognition, 114998.